



User Guide

Blue Team Training Toolkit (BT3)

27th of August 2016

Version	Date	Comment
2.0	27/08/2016	Changes introduced by BT3 v2.0 have been included.

Juan J. Güelfo
Lead IT-security consultant at Encrypto AS

Table of Contents

1. Introduction.....	3
1.1 What is Blue Team Training Toolkit?.....	4
1.2 Who Should Use Blue Team Training Toolkit?.....	6
1.3 System Requirements.....	6
1.4 Disclaimer.....	6
1.5 Blue Team Training Toolkit License.....	7
1.6 Blue Team Training Toolkit Content Subscription Terms and Conditions.....	7
2. Getting Started with Blue Team Training Toolkit.....	8
2.1 Download and Installation.....	8
2.2 Directory Structure.....	9
2.3 Interactive Command-Line Interface.....	10
2.4 Blue Team Training Toolkit Content Subscription API.....	12
3. BT3 Module: Maligno.....	16
3.1 Getting Started.....	17
3.2 Malware Indicator Profiles.....	20
3.3 Setting up Maligno.....	22
4. BT3 Module: Pcapteller.....	25
4.1 Getting Started.....	25
4.2 PCAP Metadata Modules.....	28
4.3 Setting up Pcapteller.....	29
4.4 Creating a Network Diversion.....	30
5. Support.....	33
6. Known Bugs and Limitations.....	33

1. Introduction

Until the past decade, common threats against computer systems could be stopped by anti-virus software and firewalls. Nowadays, these two countermeasures can be easily bypassed by attackers, and they just offer a basic degree of protection. Moreover, IT personnel are required to have specialized skills within computer network defense analysis and incident response in order to detect, analyze and react effectively to computer threats.

Computer network defense analysis is a broad topic and skills can be acquired with different methods. Common training techniques are based on studying network traffic that could be either live or previously captured.

In any of these situations, the production and acquisition of network traffic requires an attack scenario with supporting infrastructure. The goal is to successfully monitor the network traffic while the attack is in progress. The result allows a blue team to improve their skills, test the detection tools deployed as part of an organization's IT infrastructure, and ultimately exercise their incident response plan.

Currently, the possibilities for training and improving in these disciplines have important constraints mainly related to these criteria:

- **Difficulty of implementation**
This criterion describes how difficult it is to create, configure and maintain an environment where the attack scenario is going to be executed. The difficulty of implementation is usually related to the amount of time required for the tasks. An ideal environment would involve low-time and low-work requirements.
- **Cost**
This criterion defines the amount of resources required for the correct implementation of the attack scenario. The lower the cost is, the smaller amount of money an organization will need to invest on its training program. Alternatively, low costs will allow organizations to design more complete training programs with the same budget.
- **Risk**
This criterion describes the danger that a production network faces when an attack scenario is executed during a training session. Risk can be understood as the combination of likelihood and impact associated to an event. Therefore, the lower the risk is, the safer the training environment will be.
- **Realism**
This criterion describes the level of detail that a training environment replicates based on what a real case would be. The higher the realism is, the closer to reality the training environment will be.

Typically, the criteria described in the previous sections tend to present themselves with important dilemmas, which force organizations to prioritize one criterion over others, or just reach a compromise that falls far from an optimal training session.

Let's illustrate such dilemmas with three common examples:

- **Efficiency versus Realism**
Network traffic produced in attack scenarios (purposed for training sessions) can be captured and saved as PCAP files. From a training perspective, such files contain a "story" specific to the environment where it was captured, and it can be used again by a blue team, for example when training new members or reviewing a training exercise.

This reusability may not be optimal when multiple organizations cooperate and exchange network traffic, in an attempt to conduct more efficient training sessions. Using network traffic produced by

external parties removes the creation of new attack scenarios from the equation. This reduces the cost and the preparation of a training session. However, it usually translates into less realism, since the use of network traffic produced in external networks will not match the organization's environment.

An ideal situation would allow organizations to cooperate, exchange network traffic and customize it to their needs. This would reduce costs and difficulty of implementation, while increasing network traffic reusability and realism.

- **Risk versus Realism**

In order to train computer network defense analysts and reach an advanced skill level, it is essential to create realistic attack scenarios that can generate relevant network traffic. In many cases, real pieces of malware are used in such scenarios, so computer network defense analysts can train with real indicators. However, this practice comes with an inherent risk.

On one hand, an attempt to reduce risk usually results in less realistic training sessions (e.g. not training in production environments). On the other hand, realistic scenarios tend to elevate risk. An optimal scenario should allow organizations to train in safe conditions, while keeping a high degree of realism.

- **Risk versus Cost**

Running low-risk training sessions tends to increase costs, because more resources and preparation are required. Assuming a training session is going to be conducted in a production network, organizations will typically try to reduce risk as much as possible. Two common scenarios can represent the dilemma.

On one hand, if real malware samples are used, reverse engineering or other research against the sample should be conducted. This will provide the organization with clear guidelines of how to work with the sample, and what to expect if something goes wrong. Reverse engineering requires extra preparation time and knowledge, which is usually translated into higher costs. If the organization does not want to spend such amount of resources, it should be prepared to accept a higher risk during the training session.

On the other hand, organizations could use specialized commercial software for malware simulation and/or an external Red Team. While this alternative tends to be a safe approach, it rapidly increases the costs of the training session. Companies with significant resources and mature security programs are usually the ones who can benefit from this approach, rather than organizations with constraints.

1.1 What is Blue Team Training Toolkit?

Blue Team Training Toolkit (BT3) introduces improvements in current computer network defense analysis training. Based on adversary replication techniques, and with reusability in mind, BT3 allows individuals and organizations to create realistic computer attack scenarios, while reducing infrastructure costs, implementation time and risk.

The Blue Team Training Toolkit is written in Python, and it follows an open source FreeBSD license.

The most important features of BT3 include:

- **Adversary replication and malware simulation**

BT3 includes the latest version of Encrypto's Maligno. This module is designed with a client-server architecture, and it allows blue teams to simulate malware infections or targeted attacks with specific C&C communications in a safe manner.

BT3 is also shipped with multiple malware indicator profiles that ensure a "plug & play" experience, when planning and preparing a training session. Furthermore, malware indicator profiles can be developed easily, something that contributes to lower preparation costs and better cooperation.

- **Network traffic manipulation and replay**

BT3 includes Encripto's Pcapteller, a module designed for traffic manipulation and replay. Pcapteller can customize and replay network traffic stored in PCAP files. This allows blue teams not only to re-create scenarios where computer attacks or malware infections occurred, but also make it look like everything is really happening in their own network.

- **Ease of use and flat learning curve**

Information security tools usually implement their own options, syntax and commands. Mastering a tool can therefore take some time.

To ensure usability from the first moment, and not waste lots of valuable time, BT3 uses an interactive command-line interface inspired by Rapid7's Metasploit Framework (MSF). Since MSF is a tool well-known by information security professionals, it makes sense to provide some degree of familiarity. This means that learning how to use BT3 should take a minimum effort, and most blue teams will be able to focus on their training session, rather than figuring out how to use a new tool.

- **Blue team cooperation and network traffic reusability**

On one hand, BT3 can contribute with flexible malware indicator profiles that can be exchanged or distributed among organizations. Also, it helps blue teams train with a high degree of realism, without the need of using real malware. This is a key area that solves the "Risk versus Realism" and the "Risk versus Cost" dilemmas.

On the other hand, BT3 offers a platform that improves efficiency, by reducing preparation time and infrastructure costs. The ability to customize captured network traffic can allow organizations to reuse and exchange PCAP files, while keeping a decent degree of realism. This reusability also ensures a better Return On Investment, since the network traffic of a training session can be customized and reused without setting up the whole original attack scenario. This addresses the "Efficiency versus Realism" dilemma.

- **Content subscription (optional)**

Blue Team Training Toolkit provides both free and premium training content ready for use. This allows individuals and organizations to train with relevant cases without the burden of creating attack scenarios and recording network traffic manually, or spending time on developing new malware indicator profiles.

Premium content can be purchased with pre-paid credits directly from BT3 command line interface, and it follows a Personal or Enterprise license (more details are covered later).

Content subscription is an optional feature in the Blue Team Training Toolkit. This means that BT3 can still be used in offline mode if desired, with the same experience as in version 1.x.

Despite BT3 aims for blue teams, it could also become a powerful resource for red teams. In such context, BT3 module could assist with the creation of a decoy or a diversion during an engagement.

Let's consider advanced security assessments that result in access to the target's internal network. Such access could be obtained in multiple ways, for example by using social engineering against employees, compromising weak internet-facing systems, or just as starting point if the engagement assumes compromise.

In environments with tight network countermeasures and a (proactive) blue team in place, red teams must measure their movements across the target network, in order to fly under the radar.

Occasionally, red teams may perform actions in the network that could draw a blue team's attention. Using BT3 in combination with VPN pivoting, red teams could create a network diversion. In other words, this could make a blue team see ghosts, letting a red team hide in plain sight.

1.2 Who Should Use Blue Team Training Toolkit?

Blue Team Training Toolkit has been designed for computer network defense analysis training, and it could be used by public and private organizations, as well as training institutions such as universities. In addition, BT3 could assist red teams during specific scenarios that may occur during the course of a security engagement.

1.3 System Requirements

Blue Team Training Toolkit requires the following minimum hardware configuration:

- +500 Mhz processor.
- 1 GB RAM available.
- 100 MB available disk space.
- 10/100 Mbps network interface.

Access to online material provided by a Blue Team Training Toolkit content subscription has the following minimum requirements:

- 256 kbps internet connection.
- An active subscription bound to Personal or Enterprise license. Downloading premium content is optional, and requires pre-paid credits available in your account.

The following operating systems are officially supported by Blue Team Training Toolkit:

- Kali Linux x64, with Python 2.7.
- Ubuntu 16.04 LTS, with Python 2.7.

Blue Team Training Toolkit requires **Python 2.7.9** or newer. Python 3.x is not supported at the moment.

BT3 has been successfully tested on physical hosts and virtual machines (VirtualBox 5.0). The software should also run on other Debian-based distributions. However, no further testing has been done so far.

BT3 depends on “python2.7”, “python-scapy” and “python-ipcalt” packages. It also uses OpenSSL for generating a server certificate during the installation process. The BT3 installer will take care of these dependencies automatically. Given the nature of the functionality implemented in BT3, the software must run with root or sudo privileges.

Clients generated by BT3’s Maligno module have been successfully tested on Windows and Linux hosts. Clients can be executed as regular Python scripts, or compiled with PyInstaller 2.x / 3.x. Successful script execution or PyInstaller compilation will require Python 2.7. No elevated privileges are required in order to run Maligno client scripts.

1.4 Disclaimer

Blue Team Training Toolkit (BT3) can only be used for legal activities.
Use this software at **your own risk**.

It is the user's responsibility to obey all applicable laws. The developer or Encripto AS assume no liability, and are not responsible for any misuse or damage caused by this program.

Any of the trademarks, service marks, collective marks, design rights, personality rights or similar rights that are mentioned, used or cited in this document is property of their respective owners.

Read the license section in this document for more details.

1.5 Blue Team Training Toolkit License

Blue Team Training Toolkit (BT3) is licensed under the FreeBSD license.
Read <http://www.freebsd.org/copyright/freebsd-license.html> for more details.

Blue Team Training Toolkit (BT3). Written by Juan J. Güelfo.
Copyright 2013-2016 Encripto AS. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY ENCRYPTO AS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL ENCRYPTO AS, THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of Encripto AS.

1.6 Blue Team Training Toolkit Content Subscription Terms and Conditions

Before you start using Blue Team Training Toolkit content subscription, you need to read carefully and accept the terms and conditions listed at <https://www.bt3.no/terms-conditions/>

2. Getting Started with Blue Team Training Toolkit

This section is going to cover the most fundamental aspects of Blue Team Training Toolkit (BT3) that will get you started in no time.

2.1 Download and Installation

BT3 is distributed as a tarball file, and it can be downloaded from <https://www.encripto.no/tools>. Once the file is on your hard disk, proceed to extract it and run the installer as shown below:

```
root@kali:~# tar -xvzf BT3-2.0.tar.gz
BT3-2.0/BT3.py
BT3-2.0/profiles/oldrea.py
BT3-2.0/libs/bt3out.py
BT3-2.0/modules/maligno_client.py
```

Fig. 1: Terminal output during tarball extraction

```
root@kali:~# cd BT3-2.0/
root@kali:~/BT3-2.0# ./install.sh
```

Fig. 2: Running the BT3 installer

```
=====
| Blue Team Training Toolkit - Install Script |
| by Juan J. Guelfo, Encripto AS (post@encripto.no) |
|=====|
[*] Installing dependencies...
Hit:1 http://nl.mirror.babylon.network/kali kali-rolling InRelease
Reading package lists... Done
Reading package lists... Done
Building dependency tree
Reading state information... Done
```

Fig. 3: Installer progress

During the installation process, the installer will proceed to create a self-signed server certificate that can be used with BT3’s Maligno module. The certificate generation process will require some information. At this point of the installation, you will have the opportunity to use default values by pressing “Enter”, or providing your own. Be aware default values could trigger IDS signatures under certain circumstances.

```
[*] Creating folders...
[+] Directory 'pcaps' successfully created.
[+] Directory 'certs' successfully created.

[*] Generating server key and certificate...

Generating a 2048 bit RSA private key
..+++
.....+++
writing new private key to 'server.key'
-----
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:
State or Province Name (full name) [Some-State]:
Locality Name (eg, city) []:
Organization Name (eg, company) [Internet Widgits Pty Ltd]:
Organizational Unit Name (eg, section) []:
Common Name (e.g. server FQDN or YOUR name) []:
Email Address []:

[*] Generating PEM...
[+] Certificate successfully generated.

[+] Installation completed!
```

Fig. 4: Self-signed certificate generation completes the installation

As soon as the certificate is generated, the installer will place it in the “certs” folder. You may add extra certificates (PEM format) to this folder for later use, if desired.

At this point, the installation process should be complete.

2.2 Directory Structure

After successfully running the installation process, your Blue Team Training Toolkit installation folder should contain a few relevant directories:

- **certs**
This folder contains SSL/TLS certificates that can be used with BT3’s Maligno module. Additional certificates (PEM format) can be placed in this directory before the module is run. After the installation process, the folder should contain a self-signed certificate ready for use.
- **pcaps**
This directory contains PCAP files (libpcap format) containing captured network traffic, which can be used with BT3’s Pcapteller module. New PCAP files must be placed in this folder before the module is run. This folder will be empty right after completing the installation process. This means that the user will have to add new PCAP files in order to successfully run the Pcapteller module.
- **profiles**
This folder contains malware indicator profiles that can be used with BT3’s Maligno module. BT3 is shipped with multiple profiles which are ready for use. New profiles can be added to this folder before running the Maligno module.

2.3 Interactive Command-Line Interface

Blue Team Training Toolkit offers an interactive command-line interface with syntax completion. This section will cover the most relevant commands supported by the application.

- **Starting Blue Team Training Toolkit**

You may start the interface by running “python BT3.py” from your Linux terminal.

```

root@kali:~/BT3-2.0# python BT3.py

Blue Team
Training Toolkit

-----
Blue Team Training Toolkit (BT3) v2.0
By Juan J. Guelfo | Encripto AS | post@encripto.no
-----

BT3 has API powers!
Create your account with apisignup and get access
to free and premium PCAP files and malware indicator profiles

BT3 >
    
```

Fig. 5: Running Blue Team Training Toolkit

- **Help overview**

A quick command overview can be obtained with the “help” command.

```

BT3 > help
Command      Description
-----
apiconnect   Connect to Blue Team Training Toolkit API with valid credentials.
apidisconnect Disconnect from Blue Team Training Toolkit API, and work in offline mode.
apinewcreds  Start a Blue Team Training Toolkit API password change or account recovery.
apiredeem <code> Redeem a Blue Team Training Toolkit credit voucher.
apisignup    Create a new Blue Team Training Toolkit API account.
back        Exit current selected module and return to main menu.
bt3update    Check for software updates.
exit        Exit the Blue Team Training Toolkit.
help        Display help menu.
resource <file> Load and enter a sequence of Blue Team Training Toolkit commands from a resource file.
show modules Display supported application modules.
show subscription Display Blue Team Training Toolkit content subscription details.
use <module> Select an application module.
version      Display software version.

BT3 >
    
```

Fig. 6: Help menu displaying general commands

- **Version check**

The application’s current version can be displayed with “version”, while “bt3update” will check for new updates.

```

BT3 > version

[*] You are running Blue Team Training Toolkit (BT3) version 2.0
    
```

Fig. 7: Results of the "version" command

```
BT3 > bt3update

[*] Checking for updates...
[+] There is a new version of the Blue Team Training Toolkit!
[+] Check https://www.encripto.no/tools for more information.

BT3 > █
```

Fig. 8: Blue Team Training Toolkit can check for new updates on demand

- **Tool modules list**

Supported application modules can be displayed with “show modules”.

```
BT3 > show modules

Module           Description
-----
maligno          Attack simulation with customized malware indicators.
pcapteller       Network traffic manipulation and replay.

BT3 > █
```

Fig. 9: List of tools (modules) contained in BT3

- **Resource files**

Blue Team Training Toolkit supports resource files, which allow you to script module commands in a simple manner. Let’s consider a resource file “test.rc” containing the following instructions:

- use maligno
- set LHOST 192.168.1.10
- set PROFILE standard
- genclient
- run

Invoking the “resource” command, with the resource file name as an argument, should execute all the instructions automatically.

```
BT3 > resource test.rc

[*] Running resource file...

[+] LHOST => 192.168.1.10

[+] PROFILE => standard

[*] Generating Maligno client...
[+] Maligno client successfully generated! Check the "clients" folder.

[*] Maligno is up and running. Press [CTRL+C] to stop...
```

Fig. 10: Loading a “test.rc” resource file

Resource files should be able to run any actions supported by a module. However, resource files can only execute commands within a single module in use.

2.4 Blue Team Training Toolkit Content Subscription API

The Blue Team Training Toolkit offers an optional content subscription via an online API, which includes realistic network traffic related to a wide range of network attacks, as well as important malware indicator profiles. The online library is growing constantly, and ensures a “plug & play” experience, when planning and preparing a training session.

The following sections document the most important aspects of creating and managing an API account.

- **API account creation**

New API accounts can be created with “apisignup”. This should start a wizard that will guide you through the creation process.

```
BT3 > apisignup
```

Fig. 11: Starting the BT3 API account creation process

The first step during the account creation process will require you to read and accept the Blue Team Training Toolkit terms and conditions. These can be found at <https://www.bt3.no/terms-conditions/>

```
[*] You are about to create a BT3 API account.
[*] Some basic information will be gathered during this process.

[*] BT3 API accounts are free, and they are bound to a content license.
[*] First of all, you must read the terms and conditions listed at https://www.bt3.no/terms-conditions
[*] You may press [CTRL+C] to abort this account registration at any time.

Do you accept the Blue Team Training Toolkit terms and conditions? [Y/N]: Y
```

Fig. 12: Step 1 - Accepting the Blue Team Training Toolkit terms and conditions

The second step will gather some basic information about you (full name).

```
[*] What may I call you?

First Name: Test
Last Name: Account
```

Fig. 13: Step 2 - Some basic personal information will be gathered

The third step will require you to choose a content license (Personal or Enterprise), according to the terms and conditions already accepted in the previous steps.

```
[*] Would you like to use a Personal or Enterprise content license?
[*] Check https://www.bt3.no/terms-conditions for more details.

License [P/E]: E
```

Fig. 14: Step 3 - Selecting a content subscription license

The fourth step asks you to provide a valid e-mail address, which will be used as user name and for password recovery purposes.

```
[*] What is your e-mail address?  
[*] This will be used as your username.  
  
E-mail: user@yourdomain.com
```

Fig. 15: Step 4 - Providing an e-mail address as user name

The fifth step will proceed to verify the given e-mail address. A security code will be sent via e-mail, and should be provided as account verification proof.

```
[*] You are about to set new credentials for your BT3 API account.  
[*] A security code will be sent to your registered e-mail address during this process.  
[*] You may press [CTRL+C] to abort this new credentials request at any time.  
  
E-mail Code: █
```

Fig. 16: Step 5 - E-mail verification process

The last step will allow you to set your credentials.

```
[*] It's time to choose a good password.  
[*] The minimum length is 10 characters, as well as a mix of lowercase and uppercase letters, digits and punctuation characters.  
[*] Passwords will not be echoed during this process.  
  
New Password:  
Confirm:
```

Fig. 17: Step 6 - Setting credentials

The your account should be ready for use at this point.

```
[+] Your credentials were successfully updated.  
[*] You may now type 'apiconnect' and log in with your account.
```

Fig. 18: Successful account creation

- **API account authentication**

Existing accounts can authenticate directly from Blue Team Training Toolkit with the “apiconnect” command. This will require and e-mail address a user name and its associated password.

```
BT3 > apiconnect  
  
[*] Please, enter your BT3 API credentials (password not echoed)  
  
E-mail: █
```

Fig. 19: Account authentication process

```
[*] Hello Test, Welcome to the BT3 with API powers!  
[*] Last login: 2016-08-23 20:46:17 (UTC)  
[*] Last failed login: Never
```

Fig. 20: Welcome message after successful authentication

- **API account details**

Authenticated accounts can check subscription details by typing “show subscription”.

```
BT3 > show subscription

[*] Blue Team Training Toolkit - Content Subscription Details
      User: Test Account
      E-mail:
      License: Enterprise
      Last login: 2016-08-24 21:08:35 (UTC)
      Last failed login: Never

[*] Blue Team Training Toolkit - Content Credit Details
      Balance: 0 credit(s)
      Last Purchase: Never
      Credit Expiry: 2016-08-24 21:07:47 (UTC)

[*] Blue Team Training Toolkit - Content Enterprise License
      License terms can be found at https://www.bt3.no/terms-conditions
```

Fig. 21: API subscription details

- **API account log out**

Authenticated accounts can log out by using the “apidisconnect” command.

```
BT3 > apidisconnect

[*] Disconnected from BT3 API. You are working in offline mode now.
```

Fig. 22: Disconnecting from the BT3 API

- **API account credentials reset**

Existing accounts may request a password change or account recovery by invoking “apinewcreds”.

```
BT3 > apinewcreds
```

Fig. 23: Requesting a new set of credentials

The first step of this process will require a valid e-mail address, associated to an existing account. A security code will be sent to such address, and the code must be provided as verification proof.

```
[*] You are about to set new credentials for your BT3 API account.
[*] A security code will be sent to your registered e-mail address during this process.
[*] You may press [CTRL+C] to abort this new credentials request at any time.

E-mail: █
```

Fig. 24: Step 1 - Account verification during new credentials request

The last step will require you to provide a new set of credentials.

```
[*] It's time to choose a good password.
[*] The minimum length is 10 characters, as well as a mix of lowercase and uppercase letters, digits and punctuation characters.
[*] Passwords will not be echoed during this process.

New Password:
Confirm:
```

Fig. 25: Step 2 - Setting new credentials

The new credentials will be ready for use as soon as the process has been completed.

```
[+] Your credentials were successfully updated.
[*] You may now type 'apiconnect' and log in with your account.
```

Fig. 26: Successful credentials reset

- **API credit voucher redemption**

Users who have purchased content credits will gain access to a credit voucher. The voucher can be redeemed with by invoking “apiredeem”, with the voucher code as argument.

Please, note that redeeming a code requires an authenticated API session.

```
BT3 > apiredeem bc309b176858e150044e2a5ce6bd77c9aadbcef53efecf5ee954ce7eb99e04f7

[+] Congratulations! Your voucher has been redeemed successfully.
[*] You can check your subscription status by typing 'show subscription'.
```

Fig. 27: Successful voucher redemption

3. BT3 Module: Maligno

Maligno is a module designed for attack simulations that require risk-free / fictive malware infections, or targeted attacks with specific C&C communications. The module follows a client-server architecture, where the server component is hosted by the same computer where BT3 is running, and the client component can be deployed on different machines if desired.




Fig. 28: Maligno clients can be distributed among multiple machines

Currently, Maligno server is integrated in the Blue Team Training Toolkit, and it runs on any of the supported operating systems covered in the system requirements section. However, Maligno clients can run on any operating system (e.g. Microsoft Windows, or Linux) as long as Python 2.7 is installed. Maligno clients can also run on Windows when compiled with PyInstaller. At the moment, client-server communications are handled via HTTP or HTTPS, since these are two of the most popular protocols used by malware these days.



Fig. 29: Maligno module components communicate over HTTP or HTTPS

Maligno clients are proxy aware, and they can handle themselves in multiple environments. Different proxy capabilities have been implemented in Maligno clients so far. These capabilities depend on what operating system a Maligno client is running on. The table listed below summarizes what connection scenarios are possible on different client platforms.

Blue Team Training Toolkit - Maligno Client			
Platform	Proxy Auth.	WPAD Auth.	Connectivity
Windows	Unauthenticated	Unauthenticated	Successful
	Basic	Basic	
	NTLM	NTLM	
*nix / OS X	Unauthenticated	Unauthenticated	Successful
	Basic	Basic	

3.1 Getting Started

The module can be invoked with “use maligno” directly from the BT3 command-line interface. You should note that the BT3 command prompt changes based on the current module in use.

```
BT3 > use maligno
BT3 ~ maligno > |
```

Fig. 30: Maligno module ready for use after invocation

- **Module version check**

The current module version can be checked with the “version” command.

```
BT3 ~ maligno > version
[*] You are running Maligno version 3.2
```

Fig. 31: Maligno version command output

- **Module help overview**

Maligno supports a range of general commands, which can be displayed with “help”.

```
BT3 ~ maligno > help
Command      Description
-----
back         Exit current selected module and return to main menu.
download <profile> Download a given profile from the Blue Team Training Toolkit cloud.
exit        Exit the Blue Team Training Toolkit.
genclient   Generate a client with the current configured settings.
help        Display help menu.
run         Run the module with the given options.
search <string> Find malware indicator profiles based on a given string.
set <option> <value> Set module option.
show options Display module options.
show profiles Display malware indicator profiles.
version     Display module version.
```

Fig. 32: List of commands supported by the module

- **Module option list**

Module options and their current values can be listed with “show options”.

```
BT3 ~ maligno > show options
Name      Setting  Required  Description
-----
LHOST     LHOST    True      IP address or FQDN to expose the C2 server on.
LPORT     LPORT    True      TCP Port to listen for connections.
PROFILE   PROFILE  True      Profile containing malware network indicators.
SSL       SSL       False     Enable server SSL/TLS support.
SSL_CERT  SSL_CERT False     Server certificate to use with SSL/TLS support.

BT3 ~ maligno > |
```

Fig. 33: Module options and their current values

Maligno Module Options	
Name	Description
LHOST	Defines the IP address or Fully-Qualified Domain Name (FQDN) where the Maligno server component will be exposed. This value is actively used by the Maligno client generation process. Maligno clients will attempt connections to the IP address or FQDN provided by this option.
LPORT	Defines the TCP port to listen for incoming connections. This value is actively used by the Maligno client generation process. Maligno clients will attempt connections to the port provided by this option.
PROFILE	Defines the name of the Maligno malware indicator profile in use. Valid profiles can be listed with “show profiles”.
SSL	Defines whether the Maligno server component will support SSL/TLS for incoming connections.
SSL_CERT	Defines the server certificate in use when SSL/TLS support is enabled. The self-signed certificate generated during the installation process is used by default. Additional certificates can be used, as long as they are placed in the “certs” directory, within the BT3’s installation folder.

- **Module option configuration**

Module option values can be set with the “set” command, the desired option and its new value.

```
BT3 ~ maligno > set LHOST 192.168.1.10
[+] LHOST => 192.168.1.10
BT3 ~ maligno > █
```

Fig. 34: Setting a new option value

- **Module material list**

Available malware indicator profiles can be listed with “show profiles”. If an API user account is already authenticated, the command will retrieve available profile information from the online library.

```
BT3 ~ maligno > show profiles
Profile      Location  Date      Price  Description
-----
cookie      Disk     2016-06-26  -----  Default profile with cookie header and random elements.
cryptowall_v3  Disk     2015-02-13  -----  Cryptowall v3 ransomware profile.
etumbot     Disk     2014-07-01  -----  Etumbot APT backdoor profile.
ghostnet_asp  Disk     2012-01-01  -----  Ghostnet APT profile based on ASP technology.
ghostnet_php  Disk     2012-01-01  -----  Ghostnet APT profile based on PHP technology.
harnig      Disk     2014-08-18  -----  Harnig trojan downloader profile.
havex       Disk     2014-03-14  -----  Havex trojan profile.
nuclear     Disk     2014-11-23  -----  Nuclear exploit kit file delivery profile.
oldrea     Disk     2014-07-07  -----  Oldrea APT backdoor profile.
putterpanda  Disk     2014-05-01  -----  Putter Panda APT profile.
standard    Disk     2016-06-26  -----  Default profile with static elements.
standard_random  Disk     2016-06-26  -----  Default profile with random elements.
upatre     Disk     2015-06-23  -----  Upatre banking trojan profile.
zemot      Disk     2014-11-23  -----  Zemot trojan profile.

[*] Available profiles: 14
```

Fig. 35: Example with available Maligno malware indicator profiles ready for use on disk

```
BT3 ~ maligno > show profiles
Profile      Location  Date      Price  Description
-----
adposhel_1  Cloud    2016-08-19  1      Adposhel adware checkin blocked by web proxy.
arid_viper_1 Cloud    2016-08-11  1      Operation Arid Viper. Malware indicators for interesting document.
arid_viper_2 Cloud    2016-08-11  1      Operation Arid Viper. Malware indicators for uninteresting document.
cerber_check Cloud    2016-08-14  1      Cerber ransomware public IP address check.
conficker_check Cloud    2016-08-12  1      Conficker malware checking external IP address.
conficker_sink Cloud    2016-08-12  1      Conficker malware with sinkhole response.
cookie      Cloud    2016-06-26  0      Default profile with cookie header and random elements.
CORESHELL  Cloud    2016-08-12  1      CORESHELL APT malware profile.
core_bot    Cloud    2016-08-10  1      Core Bot banking trojan.
cryptowall_v3 Cloud    2015-02-13  0      Cryptowall v3 ransomware profile.
enfal       Cloud    2016-08-10  1      Enfal (aka Lurid). Malware used in targeted attacks.
etumbot     Cloud    2014-07-01  0      Etumbot APT backdoor profile.
explosive   Cloud    2016-08-11  1      Explosive APT malware used by Volatile Cedar campaign.
```

Fig. 36: Fragment of the online profile library

- **Material search**

Malware indicator profiles can be easily found with the “search” command. Searches use the profile name or profile description as criterion.

```
BT3 ~ maligno > search standard
Profile      Location  Date      Price  Description
-----
standard     Disk     2016-06-26  0      Default profile with static elements.
standard_random Disk     2016-06-26  0      Default profile with random elements.

[*] Search results: 2
```

Fig. 37: Search results presented by the module

- **Material download**

Authenticated API accounts will have access to the Blue Team Training Toolkit online library, with both free and premium training material. Such material is ready for use and offers a “plug & play” experience.

Premium online training material has a price, which will be deducted from the user’s existing API credit balance. Premium downloads require users to have enough credit balance in order to complete the download. Free online material, on the other hand, can be downloaded without any costs.

Downloading online resources can be done with the “download” command, and the material name provided as an argument.

```
BT3 ~ maligno > download standard

[!] Training material will be downloaded from the cloud (costs may apply).
    Would you like to continue? [Y/N]: y

[*] Downloading...
[+] Congratulations! New training material is now available on your disk.
```

Fig. 38: Successful material download

- **Maligno client generation**

Once all required module options have been configured with valid values, it will be possible to generate a Maligno client script. Maligno clients can be generated directly from the BT3 command-line interface, with the “genclient” command. The generated client script will be placed at the “clients” folder, and it will be ready for deployment.

```
BT3 ~ maligno > genclient
[*] Generating Maligno client...
[+] Maligno client successfully generated! Check the "clients" folder.
BT3 ~ maligno > █
```

Fig. 39: Successful Maligno client generation

```
root@kali:~/BT3-2.0/clients# ls -l
total 28
-rw-r--r-- 1 root root 26546 Aug  9 19:14 maligno_client_standard.py
```

Fig. 40: Generated clients are placed in a specific location

- Module execution**
 Maligno server can be started with the “run” command. All module options are validated during this process.

```
BT3 ~ maligno > run
[*] Maligno is up and running. Press [CTRL+C] to stop...
```

Fig. 41: Maligno server is running and waiting for connections

3.2 Malware Indicator Profiles

Maligno’s malware indicator profiles are programmed in Python, and they follow an intuitive structure. The profiles are very flexible, and they can be customized either with simple modifications or with very complex functionality.

Malware indicator profiles are located in the “profiles” directory, which can be found within the Blue Team Training Toolkit’s installation folder. The profiles are divided in well structured areas:

Maligno Malware Indicator Profile Structure		
Class	Purpose	Value Visibility
Info	Gathers general information about the Maligno malware indicator profile.	BT3’s command-line interface.
Request	Defines the indicators that Maligno clients will use when sending requests.	Network traffic.
Response	Defines the indicators that Maligno server will use when responding to client requests.	Network traffic.
Network	Defines protocol specific configurations, as well as communication parameters.	Network traffic.

The table listed below explains the purpose of each class attribute:

Maligno Malware Indicator Profile Attributes		
Class	Attribute	Purpose
Info	author	Defines who made the malware indicator profile.
	Date	Describes when the profile was created.
	description	Provides a summary of what kind of communications or malware indicators the profile attempts to simulate. This field will be visible on the BT3's "show profile" command output.
	license	Describes the license model applied to the profile.
	references	Includes links to threat intelligence reports or other materials that backup the behavior represented by the profile.
Request	method	HTTP request method to use by client requests. Possible values are "GET", "POST" or "HEAD".
	URI	Defines the URI portion of HTTP client requests. The attribute is a list. When several comma-separated values are provided, Maligno clients will pick a URI randomly for each request.
	body	Defines the body portion of HTTP client requests. The body should be used with POST requests. However, BT3 will not complain if a body is provided with other request methods (even if the requests are malformed).
	headers	Defines the HTTP headers included in HTTP client requests. Maligno clients will attempt to honor the header order. The attribute is a list of comma-separated dictionaries.
Response	code	Defines the HTTP response code (type of response) sent by the server.
	banner	Defines the web server banner disclosed by the server, which is included as a response header.
	body	Defines the response body. This is the actual data sent in the response.
	headers	Defines the HTTP headers included in HTTP server responses. Maligno server will attempt to honor the header order. However, this is not guaranteed. The attribute is a list of comma-separated dictionaries.
Network	protocol	Defines the type of HTTP protocol to be used in client requests. Possible values are "HTTP/1.0" or "HTTP/1.1".

	encoding	<p>Defines the type of encoding to apply to the response body. This will give the server response a different look on the wire. Possible values are “None”, “Base64”, “Hex” or “Bin”.</p> <p>Please, note that the encoding applies to the whole response body. If you would like to encode just specific parts of the response body, you should use “None” as encoding, and implement your own encoding logic within the profile’s functionality. Check the modules shipped in BT3 for implementation examples.</p>
	delay	<p>Defines the amounts of seconds that Maligno client will wait before sending a request. The value is a non-negative value (greater or equal to zero).</p> <p>Note that a delay of “0” seconds will generate a huge amount of requests in a short period of time.</p>
	jitter	<p>Defines a random deviation that will be added to the delay time. The value is understood as percentage of the delay time.</p> <p>For example, a delay time of 10 seconds and a jitter of 50% will result in a maximum waiting time of 15 seconds.</p>

3.3 Setting up Maligno

This section will illustrate how to setup up BT3’s Maligno with a practical example. In this case, Maligno will be used during the simulation of a targeted attack. A piece of malware known as “Havex” or “Oldrea” has been actively used against western energy companies in the past.

Symantec has documented several cases in a report that describes network indicators associated to Havex. BT3 includes a Maligno malware indicator profile based on such report, and it will mimic the malware’s network behavior without risking any infection.

Before starting the actual setup, this case will assume that a blue team has already deployed some minimal infrastructure for network traffic monitoring. In addition, Snort with ET GPL rule set will be used as Intrusion Detection System.

- **Step 1: Configure the module options**

In this case, the “oldrea” profile should be configured as well as the server’s IP address. Communications will go over HTTP and they will use the standard port TCP 80 (default).

```

BT3 > use maligno
BT3 ~ maligno > set PROFILE oldrea

[+] PROFILE => oldrea

BT3 ~ maligno > set LHOST 192.168.1.10

[+] LHOST => 192.168.1.10

BT3 ~ maligno > show options

Name           Setting      Required  Description
-----
LHOST          192.168.1.10 True      IP address or FQDN to expose the C2 server on.
LPORT          80           True      TCP Port to listen for connections.
PROFILE        oldrea       True      Profile containing malware network indicators.
SSL            False        False     Enable server SSL/TLS support.
SSL_CERT       server.pem   False     Server certificate to use with SSL/TLS support.

BT3 ~ maligno >
    
```

Fig. 42: Module options after configuration

- **Step 2: Generate and deploy your Maligno client script**

A Maligno client script should be successfully generated once the module has been configured. Client scripts should be then deployed on those hosts that will simulate the infection or should be considered as compromised.

```
BT3 ~ maligno > genclient
[*] Generating Maligno client...
[+] Maligno client successfully generated! Check the "clients" folder.
BT3 ~ maligno > █
```

Fig. 43: Successful Maligno client generation

- **Step 3: Start the server and run the client**

The Maligno server component can be started directly from BT3's interactive interface. The Maligno client, on the other hand, should be invoked from the machines where the scripts were deployed.

```
BT3 ~ maligno > run
[*] Maligno is up and running. Press [CTRL+C] to stop...
=====
[*] New request from 192.168.1.11...
192.168.1.11 - - [24/Jun/2016 17:04:14] "POST /wp08/wp-includes/dtc
la.php?d=285745296322896178920098FD80-20&v1=038&v2=170393861&q=5265
882854508EF958F979E4 HTTP/1.1" 200 -
[+] Request served!
[*] End of request.
=====
```

Fig. 44: Maligno server running and receiving a client request during the course of the exercise

```
=====
Blue Team Training Toolkit (BT3)
Maligno module v3.2
-----
By Juan J. Guelfo | Encripto AS | post@encripto.no
=====
[*] Maligno client module is running. Press [CTRL+C] to stop...
[*] Preparing request #2...
[*] Sending request via direct connection...
[+] Request sent...
[*] Sleeping 5s...
```

Fig. 45: Maligno client output during execution

- **Step 4: Traffic analysis**

The network communications should present patterns based on the malware indicators configured in the profile. Network equipment and packet captures should register the activity at this point.

Src IP	SPort	Dst IP	DPort	Pr	Event Message
192.168.1.10	80	192.168.1.11	42327	6	ET TROJAN Havex RAT CnC Server Response HTML Tag

Fig. 46: Snort IDS alert triggered by the network activity

Encripto AS – Blue Team Training Toolkit

```
POST /wp08/wp-includes/dtcla.php?d=285745296322896178920098FD80-20&v1=038&v2=170393861&q=5265882854508EFC958F979E4 HTTP/1.1
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 6.1; en-US) AppleWebKit/525.19 (KHTML, like Gecko) Chrome/1.0.154.36
Safari/525.19
Host: toons.freeseexycomics.com
Content-Length: 0
Cache-Control: no-cache

HTTP/1.1 200 OK
Server: Apache/1.3.37 (Unix)
Date: Fri, 24 Jun 2016 15:16:32 GMT
Content-Type: text/html
Transfer-Encoding: chunked
Connection: keep-alive
Cache-Control: no-cache
Content-length: 1231

9f65-html<>head<mega http-equiv='CACHE-CONTROL' content='NO-CACHE'></head><body>No data!<!--havexQ1po0TFBWSZTW
WYvDI0B0sD//////////4oB+93V V Xu69DuN7Xyzs9y
t49QuesVxhmVlDdXpV5XZ3QmDBBERja0twTFdJV3NGV0RuUm5LY01Ya2NiY3lCb1VLahZxcVdzTLRcNhKwkhCYVvWawZnZUVZaUtDRHRJv0NpY0N052lWanlS5
25myWLDTUNsT0ZjWFB4bHlidU13Y3R5WxVjSHN5bVRXUFVpUXNRUGlEcm5Lb1ppakt1R2NtS25semJYVHNqTUFjd1JB2VmQmthY0dIZ0Z3cFBWUULFYWJ3Vh1We
E5NbVZORGnmeVnpSWx1bEfaTEVLbW9vUER3dFl0bFZaV1lIwKZLV1BDQ1lCbkvqUp3ZGR6Qmh4ZVd3c2lUeUZEUndXUW16VW55EJ1V1BRHRIZG52UHRUQkt0U
3d0SEh2VnVkwVvT1lESk9ZundheXZVQmLQZw1009wa3JWU3ZaQkhLU1YaXlqTxp0YUd66mxoWHRVd2R5cmxHd1GRXpYREpT01N5UK1aQXluand4U2tGck9Cd
WFTZEEdScnJZU2t2cW9jQ1njc0d1bmZiCWNTU3BDeLpLWgdhR3JW00pMcw1PTVZIUfVnc1Nh081FU1BseLROskhYb0lNenJsyXJ00nZzaFBJbxVtbfNhcKpZRGtVU
2ZRVHhsY0pTVGNjb1BkQvBnlJlVmVTQutYRFN0Z2NzWlvtCEFFVxG51pHdVNBdFh1V01LRnNGU0ZzaX0WgdrZUXckRhgN0dEF1V3lVktHZlFtYdxRU5Kc
GR0RVBKTldxdmNRGhCwkHieH5R1V6T25zeUxCU0FkeGV6R21ReLFEEemptY0h5SERjUFNlSm5FVEZvVmxCcFNBDULmR0lneWJYeEt6Q3NodExwbkNR3Vgck1LR
KLHSFZ5cU9Z5GpRS1F0RWRudFRJT1B3VUV0U0NTS1hYZEXIR2tC+yUW3zFTXWA0stsCwCckdw5
AHS06vbbCu7GputP5S5fGPCAkXcA00ICmsqlACGYEhAQ3v9eDM92D/8XckU4UJBMlWynA==havex--></body></head>
```

Fig. 47: One of the HTTP requests captured during the course of the exercise (UTC time zone)

4. BT3 Module: Pcapteller

Pcapteller is a module designed for network traffic manipulation and replay. It allows organizations to re-create a recorded network traffic scenario that occurred in a foreign network, as it really happened in their own infrastructure.

In a nutshell, Pcapteller reads network packets from a PCAP file, and replays them into the network. The module allows packet manipulation (MAC and IP addresses at this moment) prior to replay, so it is possible to customize the traffic with specific addresses that fit your environment.

The module is useful if you want to re-create scenarios where computer attacks or malware infections occurred. Using such scenarios as a base, Pcapteller will allow you to reuse existing PCAP files and make everything look like the attack is really happening in your own network. Pcapteller can help you improving your blue team's network security monitoring skills, or creating network diversions during red team operations.

4.1 Getting Started

The module can be invoked with “use pcapteller” directly from the BT3 command-line interface. You should note that the BT3 command prompt changes based on the current module in use.

```
BT3 > use pcapteller
BT3 ~ pcapteller > |
```

Fig. 48: Pcapteller module ready for use after invocation

- **Module version check**

The current module version can be checked with the “version” command.

```
BT3 ~ pcapteller > version
[*] You are running Pcapteller version 1.4
```

Fig. 49: Pcapteller version command output

- **Module help overview**

Pcapteller supports a range of general commands, which can be displayed with “help”.

```
BT3 ~ pcapteller > help

Command      Description
-----
back         Exit current selected module and return to main menu.
download <pcap> Download a given PCAP file from the Blue Team Training Toolkit cloud.
exit        Exit the Blue Team Training Toolkit.
help        Display help menu.
run         Run the module with the given options.
search <string> Find PCAP files based on a given string.
set <option> <value> Set module option.
show options Display module options.
show pcaps  Display PCAP files.
version     Display module version.
```

Fig. 50: List of commands supported by the module

- **Module material list**

PCAP files available for use can be listed with “show pcaps”. If an API user account is already authenticated, the command will retrieve available PCAP information from the online library.

Encripto AS – Blue Team Training Toolkit

```
BT3 ~ pcapteller > show pcaps
-----
Pcap          Size (MB)  Location  Date       Price  Description
-----
demo.pcap     0.0       Disk      2016-08-10  -----
Empty PCAP file with a local PCAP metadata module.

[*] Available PCAP files: 1
```

Fig. 51: Example with available PCAP files on disk

```
BT3 ~ pcapteller > show pcaps
-----
Pcap          Size (MB)  Location  Date       Price  Description
-----
agenttesla 1   0.02      Cloud    2016-08-16  1      Agent Tesla keylogger network traffic.
agenttesla 2   4         Cloud    2016-08-16  1      Agent Tesla keylogger delivered by DOCX dropper, plus some web surfing.
apple_fake    0.343     Cloud    2016-08-16  1      Fake Apple site visited by user, with dummy credentials submission.
bladabindi_no_c2 0.072     Cloud    2016-08-14  0      Bladabindi trojan cannot reach C2 server.
cerber_ransom 3.6       Cloud    2016-08-13  1      Cerber ransomware infection.
chinese_risk  0.796     Cloud    2016-08-22  1      Traffic related to Chinese 'riskware'.
cryptxxx_ransom 20.8     Cloud    2016-08-13  1      Cryptxxx infection through EK hosted by compromised web site.
CVE-2012-0158_payload 0.406     Cloud    2016-08-16  1      CVE-2012-0158 exploit downloads its payload successfully.
demo          0.001     Cloud    2016-08-13  0      Empty PCAP file with a simple PCAP metadata module.
```

Fig. 52: Fragment of the online PCAP library

- **Material search**

Available PCAP files can be easily found with the “search” command. Searches use the PCAP file name or its description as criterion.

```
BT3 ~ pcapteller > search demo
-----
Pcap          Size (MB)  Location  Date       Price  Description
-----
demo.pcap     0.0       Disk      2016-08-10  -----
Empty PCAP file with a local PCAP metadata module.

[*] Search results: 1
```

Fig. 53: Search results presented by the module

- **Material download**

Authenticated API accounts will have access to the Blue Team Training Toolkit online library, with both free and premium training material. Such material is ready for use and offers a “plug & play” experience.

Premium online training material has a price, which will be deducted from the user’s existing API credit balance. Premium downloads require users to have enough credit balance in order to complete the download. Free online material, on the other hand, can be downloaded without any costs.

Downloading online resources can be done with the “download” command, and the material name provided as an argument.

```
BT3 ~ pcapteller > download demo

[!] Training material will be downloaded from the cloud (costs may apply).
    Would you like to continue? [Y/N]: y

[*] Downloading...
[+] Congratulations! New training material is now available on your disk.

[!] PCAP material may contain infected files.
[!] Use caution when exporting objects from the network traffic.
```

Fig. 54: Successful material download

- **Module option list**

Module options and their current values can be listed with “show options”.

```
BT3 ~ pcapteller > show options
Name      Setting  Required  Description
----      -
FILE      True     True      Pcap file to replay in libpcap format.
FRAGMENTATION  False   True      Fragment packets during replay. Useful for networks with low MTU.
INTERFACE  True     True      Network interface to replay the packets with.
MTU       1500    True      MTU to use with packet fragmentation.
PCAP_IP_LIST  False   False     Comma-separated list of IP addresses to replace as seen on the pcap file.
PCAP_MAC_LIST  False   False     Comma-separated list of MAC addresses to replace as seen on the pcap file.
REAL_TIME  False   False     Honor inter-arrival delays while replaying packets.
WIRE_IP_LIST  False   False     Comma-separated list of IP addresses to replay as seen on the wire.
WIRE_MAC_LIST  False   False     Comma-separated list of MAC addresses to replay as seen on the wire.

BT3 ~ pcapteller > |
```

Fig. 55: Module options and their current values

Pcapteller Module Options	
Name	Description
FILE	Defines the PCAP file (libpcap format) to manipulate and replay. The file must be located in the “pcaps” directory, within the BT3’s installation folder.
FRAGMENTATION	Defines whether packet fragmentation should be enabled. This option is useful in cases where the PCAP file includes packets larger than the target network’s MTU.
INTERFACE	Defines the local network interface to use in order to replay the packets.
MTU	Defines the MTU size when packet fragmentation is in use. The MTU size must be an integer between 1 and 9000 bytes.
PCAP_IP_LIST	Defines a comma-separated list of IP addresses to replace. The IP addresses must be defined as seen in the PCAP file. The IP addresses defined in the PCAP_IP_LIST will be replaced by the same element index of the WIRE_IP_LIST.
PCAP_MAC_LIST	Defines a comma-separated list of MAC addresses to replace. The MAC addresses must be defined as seen in the PCAP file. The MAC addresses defined in the PCAP_MAC_LIST will be replaced by the same element index of the WIRE_MAC_LIST.
REAL_TIME	Defines whether inter-packet arrival timing should be honored. When this option is enabled, Pcapteller will not inject the network packets at once. Instead, it will honor the time elapsed between the arrival of each packet contained in the PCAP file. This provides a very realistic timing when analyzing a chain of events produced by the simulation.
WIRE_IP_LIST	Defines a comma-separated list of IP addresses to inject during the traffic manipulation phase. Such addresses will be visible on the wire during the traffic replay. The IP addresses defined in the PCAP_IP_LIST will be replaced by the same element index of the WIRE_IP_LIST.
WIRE_MAC_LIST	Defines a comma-separated list of MAC addresses to inject during the traffic manipulation phase. Such addresses will be visible on the wire during the traffic replay. The MAC addresses defined in the PCAP_MAC_LIST will be replaced by the same element index of the WIRE_MAC_LIST.

- **Module option configuration**

Module option values can be set with the “set” command, the desired option and its new value.

```
BT3 ~ pccapteller > set INTERFACE eth0
[+] INTERFACE => eth0
BT3 ~ pccapteller > █
```

Fig. 56: Setting a new option value

- **Module execution**

Once all required module options have been configured with valid values, Pccapteller can begin to replay packets with the “run” command. All module options are validated prior to execution.

```
BT3 ~ pccapteller > run
[*] Pccapteller started at 21:49:12. Press [CTRL+C] to stop.
[*] Reading "/root/BT3-2.0/pcaps/test.pcap"...
[+] 4085 packet(s) found.
[*] Processing 4085 of 4085 packet(s) | Error: 0 packet(s).
[*] Replaying packet(s) via eth0...
[+] Replay complete.
[*] Pccapteller finished at 21:49:17.
BT3 ~ pccapteller > █
```

Fig. 57: Successful packet replay with Pccapteller

4.2 PCAP Metadata Modules

In order to present metadata related to PCAP files already exist on disk, Pccapteller uses simple Python modules that are deployed together with the actual PCAP files. For example, “demo.py” will store metadata for “demo.pcap”.

```
BT3 ~ pccapteller > show pcaps
Pcap      Size (MB)  Location  Date      Price  Description
----      -
demo.pcap 0.0        Disk      2016-08-10  Empty PCAP file with a local PCAP metadata module.

[*] Available PCAP files: 1
```

Fig. 58: Metadata information presented by Pccapteller module

```
root@kali:~/BT3-2.0/pcaps# ls -l demo*
-rw-rw---- 1 root root 292 Aug 10 11:38 demo.pcap
-rw-rw---- 1 root root 1262 Aug 10 11:38 demo.py
```

Fig. 59: PCAP file with its metadata module deployed on disk

Metadata modules are structured as follows:

Pccapteller PCAP Metadata Module Structure		
Class	Purpose	Value Visibility
Info	Gathers general information about the PCAP file.	BT3’s command-line interface.

The table listed below explains the purpose of each class attribute:

Pcatteller PCAP Metadata Module Attributes		
Class	Attribute	Purpose
Info	author	Defines who made the PCAP file.
	Date	Describes when the PCAP file was created.
	description	Provides a summary of what kind of communications PCAP file contains. This field will be visible on the BT3's "show profile" command output.
	license	Describes the license model applied to the PCAP file.
	references	Includes links to threat intelligence reports or other materials that backup the behavior represented by the PCAP file.

4.3 Setting up Pcatteller

This section is going to demonstrate how BT3's Pcatteller module can be used during a simple training session. This case will use a public PCAP file that contains an attack scenario involving an exploit kit delivering ransomware. This PCAP file describes a chain of events where host "192.168.122.70" is the victim.

Source	Destination	Protocol	Info
192.168.122.70	144.76.161.38	TCP	49203 > http [SYN] Seq=0 Win=8192 Len=0 MSS=1460 WS=4 SACK_PERM=1
144.76.161.38	192.168.122.70	TCP	http > 49203 [SYN, ACK] Seq=0 Ack=1 Win=14600 Len=0 MSS=1367 SACK_PERM=1
192.168.122.70	144.76.161.38	TCP	49203 > http [ACK] Seq=1 Ack=1 Win=65616 Len=0
192.168.122.70	144.76.161.38	HTTP	GET /indexing_raspberries_rejuvenation_sushis/415213137352185210 HTTP/1.1
144.76.161.38	192.168.122.70	TCP	http > 49203 [ACK] Seq=1 Ack=621 Win=15872 Len=0
144.76.161.38	192.168.122.70	TCP	[TCP segment of a reassembled PDU]
192.168.122.70	144.76.161.38	TCP	49203 > http [ACK] Seq=621 Ack=1368 Win=65616 Len=0

Fig. 60: Fragment of the original PCAP file with an attacker IP address and the victim (192.168.122.70)

Let's consider an organization that would like to use such resource for a training session. The organization is interested in using its current security countermeasures and configurations in production. The production network is using a class B internal IPv4 addressing schema (172.31.0.0/16). For this example, the victim machine will become "172.31.10.11".

In this case, the following module options should be configured:

```
BT3 - pcatteller > set PCAP_IP_LIST 192.168.122.70
[+] PCAP_IP_LIST => 192.168.122.70
BT3 - pcatteller > set WIRE_IP_LIST 172.31.10.11
[+] WIRE_IP_LIST => 172.31.10.11
BT3 - pcatteller > show options
Name          Setting      Required  Description
----          -
FILE          test_pcap    True      Pcap file to replay in libpcap format.
FRAGMENTATION False        True      Fragment packets during replay. Useful for networks with low MTU.
INTERFACE     eth0         True      Network interface to replay the packets with.
MTU           1500        True      MTU to use with packet fragmentation.
PCAP_IP_LIST  192.168.122.70 False     Comma-separated list of IP addresses to replace as seen on the pcap file.
PCAP_MAC_LIST False        False     Comma-separated list of MAC addresses to replace as seen on the pcap file.
REAL_TIME     False        False     Honor inter-arrival delays while replaying packets.
WIRE_IP_LIST  172.31.10.11 False     Comma-separated list of IP addresses to replay as seen on the wire.
WIRE_MAC_LIST False        False     Comma-separated list of MAC addresses to replay as seen on the wire.
BT3 - pcatteller >
```

Fig. 61: Module options prior to traffic manipulation and replay

The result of the customized traffic injected into the network is described in the screenshots below.

```
BT3 ~ pccapteller > run

[*] Pccapteller started at 21:49:12. Press [CTRL+C] to stop.

[*] Reading "/root/BT3-2.0/pcaps/test.pcap"...
[+] 4085 packet(s) found.

[*] Processing 4085 of 4085 packet(s) | Error: 0 packet(s).
[*] Replaying packet(s) via eth0...
[+] Replay complete.

[*] Pccapteller finished at 21:49:17.

BT3 ~ pccapteller > █
```

Fig. 62: Running BT3's Pccapteller module

Source	Destination	Protocol	Info
172.31.10.11	144.76.161.38	TCP	49203 > http [SYN] Seq=0 Win=8192 Len=0 MSS=1460 WS=4 SACK_PERM=1
144.76.161.38	172.31.10.11	TCP	http > 49203 [SYN, ACK] Seq=0 Ack=1 Win=14600 Len=0 MSS=1367 SACK_PERM=1 WS=128
172.31.10.11	144.76.161.38	TCP	49203 > http [ACK] Seq=1 Ack=1 Win=65616 Len=0
172.31.10.11	144.76.161.38	HTTP	GET /indexing_raspberries_rejuvenation_sushis/415213137352185210 HTTP/1.1
144.76.161.38	172.31.10.11	TCP	http > 49203 [ACK] Seq=1 Ack=621 Win=15872 Len=0
144.76.161.38	172.31.10.11	TCP	[TCP segment of a reassembled PDU]
172.31.10.11	144.76.161.38	TCP	49203 > http [ACK] Seq=621 Ack=1368 Win=65616 Len=0

Fig. 63: Fragment of the manipulated PCAP file with attacker IP address and the victim (172.31.10.11)

Since Pccapteller injects the manipulated network traffic into the production network, existing security countermeasures can detect and alert about possible threats. This example shows how an Intrusion Detection System (Snort with ET GPL rule set) would react to the manipulated traffic.

Src IP	SPort	Dst IP	DPort	Pr	Event Message
172.31.10.11	49203	144.76.161.38	80	6	ET POLICY Outdated Windows Flash Version IE
172.31.10.11	49203	144.76.161.38	80	6	ET CURRENT_EVENTS Possible Angler EK Flash Exploit URI Structure Jan 21 2015
144.76.161.38	80	172.31.10.11	49205	6	ET CURRENT_EVENTS Angler EK XTEA encrypted binary (11) M2
144.76.161.38	80	172.31.10.11	49205	6	ET CURRENT_EVENTS Angler EK XTEA encrypted binary (13)
172.31.10.11	49206	54.93.182.214	80	6	ET POLICY Possible External IP Lookup Ipinfo.io
172.31.10.11	49207	104.27.143.176	80	6	ET TROJAN Win32/Teslacrypt Ransomware HTTP CnC Beacon M2
172.31.10.11	62658	8.8.4.4	53	17	ET TROJAN TeslaCrypt/AlphaCrypt Variant .onion Proxy Domain (lq3ahljcfceont3xx)
172.31.10.11	60626	8.8.4.4	53	17	ET POLICY DNS Query to .onion proxy Domain (tor2web)
192.251.226.206	443	172.31.10.11	49218	6	ET CURRENT_EVENTS Tor2Web .onion Proxy Service SSL Cert (1)

Fig. 64: Alerts generated by Intrusion Detection System (Snort) during the execution of the example

4.4 Creating a Network Diversion

In environments with tight network countermeasures and a (proactive) blue team in place, a red team must measure their movements across the target network, in order to fly under the radar. But, what if this is not possible? What if the red team needs to perform actions that could potentially draw the blue team’s attention?

Using BT3’s Pccapteller module in combination with VPN pivoting, a red team could create a network diversion. In other words, this could make a blue team see ghosts through packet captures and/or deployed Intrusion Detection Systems. Here you have an example on how this works in practice:

- Step 1: Assumptions**
 Let’s assume that the red team has already deployed a VPN tunnel towards the target network. The red team has also some basic target network visibility. In other words, they know about MAC addresses or the IP address schema of the target network.

For the sake of this explanation, the target network will be “192.168.1.0/24”, with a Palo Alto appliance (MAC address “00:1b:17:00:00:02”) as gateway. The target network is also running Snort as Intrusion Detection System.

The red team has also a PCAP file containing the chain of events and the network indicators related to an exploit kit attack with a successful ransomware infection. Alternatively, network traffic with custom indicators could be generated and captured with other tools, such as BT3’s Maligno module and Wireshark.

- **Step 2: Preparing your ghosts**

Based on information gathered during the engagement, the red team should pick a set of MAC addresses that fits the target environment. The same applies to internal IP addresses that may be used as decoys, in an attempt to draw the blue team’s attention.

In this specific example, the PCAP file was downloaded from <http://malware-traffic-analysis.net>, and it shows host “10.3.23.102” as victim. The MAC address of the gateway used by such host is “20:e5:2a:b6:93:f1”.

No.	Time	Source	Destination	Protocol	Len
1	15:42:17.722	10.3.23.102	23.229.205.72	TCP	
2	15:42:17.844	23.229.205.72	10.3.23.102	TCP	
3	15:42:17.844	10.3.23.102	23.229.205.72	TCP	
4	15:42:17.845	10.3.23.102	23.229.205.72	HTTP	
5	15:42:17.845	23.229.205.72	10.3.23.102	TCP	


```

Frame 3: 60 bytes on wire (480 bits), 60 bytes captured (480 bits)
Ethernet II, Src: HewlettP_1c:47:ae (00:08:02:1c:47:ae), Dst: Netgear_b6:93:f1 (20:e5:2a:b6:93:f1)
  Destination: Netgear_b6:93:f1 (20:e5:2a:b6:93:f1)
  Source: HewlettP_1c:47:ae (00:08:02:1c:47:ae)
  Type: IPv4 (0x0800)
  Padding: 000000000000
Internet Protocol Version 4, Src: 10.3.23.102, Dst: 23.229.205.72
Transmission Control Protocol, Src Port: 49309 (49309), Dst Port: 80 (80), Seq: 1, Ack: 1, Len: 0
    
```

Fig. 65: Fragment of the original contents of the PCAP file

- **Step 3: Sending traffic**

In order to deploy a realistic decoy that can drive network countermeasures crazy, and hopefully confuse the blue team, the red team will manipulate and replay traffic with BT3’s Pcapteller module over the existing VPN tunnel.

In this case, the original host under attack will be replaced with “192.168.1.111” (a random host in the target network), and the original gateway’s MAC address will be replaced with the Palo Alto appliance’s “00:1b:17:00:00:02”. All manipulated traffic will be replayed over the VPN tunnel interface “vpn0”. With such decisions made, Pcapteller can be configured like this:

```

BT3 - pcapteller > show options
Name          Setting          Required  Description
----          -
FILE          decoy.pcap       True      Pcap file to replay in libpcap format.
FRAGMENTATION False            True      Fragment packets during replay. Useful for networks with low MTU.
INTERFACE     vpn0              True      Network interface to replay the packets with.
MTU           1500              True      MTU to use with packet fragmentation.
PCAP_IP_LIST  10.3.23.102      False     Comma-separated list of IP addresses to replace as seen on the pcap file.
PCAP_MAC_LIST 20:e5:2a:b6:93:f1 False     Comma-separated list of MAC addresses to replace as seen on the pcap file.
REAL_TIME     False            False     Honor inter-arrival delays while replaying packets.
WIRE_IP_LIST  192.168.1.111   False     Comma-separated list of IP addresses to replay as seen on the wire.
WIRE_MAC_LIST 00:1b:17:00:00:02 False     Comma-separated list of MAC addresses to replay as seen on the wire.

BT3 - pcapteller >
    
```

Fig. 66: Module options prior to traffic manipulation

For even a more realistic look, “REAL_TIME” support could be enabled on Pcapteller. This would honor inter-packet arrival time during the actual replay.

- **Step 4: Results**

Once the network traffic is replayed over the VPN tunnel, the countermeasures placed on the target network should register the “fake activity”.

Encrypto AS – Blue Team Training Toolkit

Src IP	SPort	Dst IP	DPort	Pr	Event Message
192.168.1.111	49331	64.20.35.186	80	6	ET TROJAN Suspicious Accept in HTTP POST - Possible Alphacrypt/TeslaCrypt
192.168.1.111	49331	64.20.35.186	80	6	ET TROJAN Alphacrypt/TeslaCrypt Ransomware CnC Beacon
103.27.87.88	80	192.168.1.111	49333	6	ET TROJAN Alphacrypt/TeslaCrypt Ransomware CnC Beacon Response

Fig. 67: Snort alerts triggered by the network diversion

Even if the blue team goes into a packet level, Wireshark will display the replayed traffic as if the infection really happened. The traffic should reflect the manipulation of both MAC and IP addresses.

Source	Destination	Protocol	Length	Info
192.168.1.111	64.20.35.186	TCP	66	49331 > 80 [SYN] Seq=0 Win=8192 Len=0 MSS=1460 WS=256 SACK_PERM=1
64.20.35.186	192.168.1.111	TCP	60	80 > 49331 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460
192.168.1.111	64.20.35.186	TCP	60	49331 > 80 [ACK] Seq=1 Ack=1 Win=16445440 Len=0
192.168.1.111	64.20.35.186	HTTP	922	POST /sysstr.php HTTP/1.1 (application/x-www-form-urlencoded)
64.20.35.186	192.168.1.111	TCP	60	80 > 49331 [ACK] Seq=1 Ack=869 Win=64240 Len=0

Fig. 68: Fragment of the replayed traffic (network decoy)

▶ Destination: PaloAlto_00:00:02 (00:1b:17:00:00:02)

Fig. 69: Destination MAC address after replay

5. Support

Encrypto AS provides technical support according to the terms and conditions described at <https://www.bt3.no/terms-conditions/>

Blue Team Training Toolkit support page can be found at <https://www.bt3.no/support/>

6. Known Bugs and Limitations

Blue Team Training Toolkit is in constant development and bugs could always happen. The following lines gathers known bugs and limitations.

- BT3's Maligno profiles with "Transfer-Encoding" header set to "chunked" are not handled properly. The value is deliberately sent as "chuncked" as a workaround.
- BT3's Maligno profiles using POST client requests and a "Keep-Alive" server response header, may cause errors in server responses. As a workaround, use "Keep-A1ive" as response header value.
- BT3's Maligno client HTTP(S) proxy awareness works with static proxies and WPAD when executed on Windows and non-Windows platforms. Supported authentication methods are anonymous, basic and NTLM (NTLM only on Windows).

WPAD is not a standard implementation. It just detects all possible proxies in the PAC and uses the first one that allows internet access. This implementation ensures internet connectivity also under some non-standard proxy configurations.

Feel free to contact post@encrypto.no for feedback, bug reports or feature requests.